

# WHISKY TIRE & RIM COMPATIBILITY CHART



RIM	MAXIMUM TIRE SIZE*	MINIMUM TIRE SIZE	ETRTO	TUBELESS READY**	TBLS™***	ASTM CONDITION****
<b>No.9 41W Carbon Trail Rim 29"</b>	29 x 3.0"	29 x 2.1"	622	x	x	3
<b>No.9 41W Carbon Trail Rim 27.5"</b>	27.5 x 3.0"	27.5 x 2.1"	584	x	x	3
<b>No.9 29W Carbon Goat Rim</b>	29 x 2.35"	700c x 32mm	622	x	x	3
<b>No.9 50W Carbon 27.5+ Rim</b>	27.5 x 3.5"	27.5 x 2.8"	584	x	x	3
<b>No.9 70W Carbon Fat Rim</b>	26 x 4.8"	26 x 3.8"	559	x		3
<b>No.9 100W Wide Carbon Fat Rim</b>	26 x 5.05"	26 x 3.8"	559	x	x	3

\* Max tire refers to the maximum recommended tire size for use with this rim. Follow manufacturers recommendations for clearance on bicycles and accessories in use.

\*\* For tubeless use, Whisky rims must be used with tubeless ready tires, tubeless rim tape, and tubeless sealant. Please refer to [whiskyparts.co/safety](http://whiskyparts.co/safety) for complete tubeless instructions.

\*\*\* True Bead Lock System

\*\*\*\* ASTM Condition definitions can be found at [whiskyparts.com/safety](http://whiskyparts.com/safety).