

# WHISKY TIRE & RIM COMPATIBILITY CHART



| RIM                                    | MAXIMUM TIRE SIZE* | MINIMUM TIRE SIZE | ETRTO | TUBELESS READY** | TBLS™ *** | ASTM CONDITION**** |
|--|--------------------|-------------------|-------|------------------|-----------|--------------------|
| <b>No.9 41W Carbon Trail Rim 29"</b>   | 29 x 3.0"          | 29 x 2.1"         | 622   | x                | x         | 3                  |
| <b>No.9 41W Carbon Trail Rim 27.5"</b> | 27.5 x 3.0"        | 27.5 x 2.1"       | 584   | x                | x         | 3                  |
| <b>No.9 29W Carbon Goat Rim</b>        | 29 x 2.35"         | 700c x 32mm       | 622   | x                | x         | 3                  |
| <b>No.9 50W Carbon 27.5+ Rim</b>       | 27.5 x 3.5"        | 27.5 x 2.8"       | 584   | x                | x         | 3                  |
| <b>No.9 70W Carbon Fat Rim</b>         | 26 x 4.8"          | 26 x 3.8"         | 559   | x                |           | 3                  |
| <b>No.9 80W Carbon Fat Rim</b>         | 27.5 x 4.8"        | 267.5 x 3.8"      | 584   | x                | x         | 3                  |
| <b>No.9 100W Wide Carbon Fat Rim</b>   | 26 x 5.05"         | 26 x 3.8"         | 559   | x                | x         | 3                  |

\* Max tire refers to the maximum recommended tire size for use with this rim. Follow manufacturers recommendations for clearance on bicycles and accessories in use.

\*\* For tubeless use, Whisky rims must be used with tubeless ready tires, tubeless rim tape, and tubeless sealant. Please refer to [whiskyparts.co/safety](http://whiskyparts.co/safety) for complete tubeless instructions.

\*\*\* True Bead Lock System

\*\*\*\* ASTM Condition definitions can be found at [whiskyparts.com/safety](http://whiskyparts.com/safety).