



FENDER MOUNT INSTRUCTIONS

Thank you for your purchase of this Whisky Parts Co. product. We strive to make high-performance parts and accessories that allow you to focus on your rides with confidence. Please take the time to register your product before hitting the trails.

⚠ WARNING

CYCLING CAN BE DANGEROUS. BICYCLE PRODUCTS SHOULD BE INSTALLED AND SERVICED BY A PROFESSIONAL MECHANIC. NEVER MODIFY YOUR BICYCLE OR ACCESSORIES. READ AND FOLLOW ALL PRODUCT INSTRUCTIONS AND WARNINGS INCLUDING INFORMATION ON THE MANUFACTURER'S WEBSITE. INSPECT YOUR BICYCLE BEFORE EVERY RIDE. ALWAYS WEAR A HELMET.

⚠ WARNING

WHISKY PARTS CO RECOMMENDS THAT ITS FORKS BE USED SOLELY WITH ISO COMPLIANT QUICK-RELEASE FENDERS. CONSULT FENDER MANUFACTURER FOR SPECIFIC COMPATIBILITY.

⚠ WARNING

DO NOT MOUNT RACKS OR ANY OTHER LOAD BEARING ACCESSORY TO THE FENDER MOUNTS. DOING SO COULD RESULT IN FORK OR FENDER MOUNT BREAKAGE, CAUSING A LOSS OF CONTROL. IF YOU ARE NOT SURE IF A DEVICE IS COMPATIBLE, CONSULT YOUR DEALER.

Additional Product and Safety Information can be found at the website - whiskyparts.com/safety

Intended Use & Compatibility

Whisky's Fender Mounts provide a removable fender mounting solution for wet weather riding.

This fender mounting system is compatible with Whisky forks that feature M5x.08 bosses at the dropout as depicted in Fig 2.

Condition 2



Intended for ASTM 2 conditions, defined as unpaved and gravel roads and trails with moderate grades. In this set of conditions, contact with irregular terrain and loss of tire contact with the ground may occur. Drops are intended to be limited to 15cm (6") or less.

Tools Required

- 8mm box end wrench
- Allen key size for set screws
- Allen key size for fender screws
- Torque wrench that measures in Nm
- Blue threadlocker

Installation Instructions

1. Remove set screws from fender mounting holes (figure 1).
2. Apply Blue threadlocker onto fender mount.
3. Thread M5 nuts onto fender mounts (figure 2).
4. Make sure the nuts are threaded onto the fender mounts at least 6-7 threads.
5. Thread fender mounts into fork leg fender-mounting holes.
6. Make sure fender mounts are threaded in at least 4 threads.
7. Thread nut up to the fork leg.
8. Make sure fender mount face is parallel with plane of the fork.
9. Tighten nut against fork leg to 3-4Nm to lock fender mount into position.
10. Check that assembly is tightened properly.
11. When installing fender into mounts and threaded crown hole, install per fender manufacturer instructions but do not exceed a maximum of 5Nm with fender hardware.
12. An M5 bolt will need to be used to mount fender crown hardware to fork. Follow fender manufacturer instructions and torque rating but do not exceed 5Nm. Apply thread locker or use a lock washer with this bolt.

Ongoing Maintenance

Periodically check to make sure all mounting bolts are properly tightened to the frame and fork, and that the fenders are properly installed per the fender manufacturer's specifications.

⚠ WARNING

FAILURE TO PROPERLY INSTALL A FRONT FENDER OR FAILURE TO ENSURE THAT ALL MOUNTING HARDWARE REMAINS PROPERLY TIGHTENED COULD ALLOW THE FENDER TO CONTACT THE FRONT WHEEL CAUSING A CRASH, RESULTING IN SERIOUS INJURY.

Warranty Registration

Proof of purchase is required before a warranty claim is processed. Whisky Parts Co. therefore strongly encourages warranty registration at whiskyparts.com/site/warranty. Failure to register will not affect consumer rights, so long as the consumer can show in a reasonable manner proof of original ownership and the date the Whisky product was purchased. If you have any questions contact warranty@whiskyparts.com.

